



特征:

- ◇ 金属化聚丙烯薄膜作为介质，串联结构
- ◇ 体积小，能承受大电流
- ◇ 损耗小，可靠性高
- ◇ 阻燃性环氧粉末封装

Features:

- ◇ Metallized polypropylene film as dielectric, series structure
- ◇ Small size, can withstand high current
- ◇ low loss, high reliability
- ◇ Flame retardant epoxy resin powder coating

用途:

- ◇ 用于电子整流器的启辉电路中
- ◇ 用于家电中

Application:

- ◇ Suitable for starter circuit in the electronic ballast
- ◇ Suitable for household appliances

外形图 Outline Drawing	
直线型 Straight lead type	成型型 Formed lead type

技术要求 Specifications	
引用标准 Reference Standard	GB 10190(IEC384—16)
气候类别 Climatic Category	40/105/21 (85~105℃) 每升高 1℃, U _R 下降 1.25%
额定电压 Rated Voltage	630V、800V、1000V、1250V
电容量范围 Capacitance Range	0.001μF~2.2μF
电容量偏差 Capacitance Tolerance	J=±5% K=±10%
损耗角正切 Dissipation Factor	≤0.001 (20℃、1KHz)
绝缘电阻 Insulation Resistance	≥50000MΩ (C _R ≤0.33 μF) ≥15000S (C _R >0.33 μF) (20℃, 1min)
耐电压 Voltage Proof	1.8U _R (5S)



外形尺寸

CAP (μ F)	630V DC					Part number	CAP (μ F)	800V DC					Part number
	W	H	T	P	d			W	H	T	P	d	
0.0015	12.5	8.5	5.0	10.0	0.6	340630152_100P_□	0.022	15.7	11.5	7.1	12.5	0.8	340800223_125P_□
0.033	12.5	10.0	6.0	10.0	0.6	341000332_100P_□	0.047	15.7	14.1	9.7	12.5	0.8	340800473_125P_□
CAP (μ F)	1000V DC					Part number	CAP (μ F)	1250V DC					Part number
	W	H	T	P	d			W	H	T	P	d	
0.0015	10.0	7.5	4.5	7.5	0.6	341000152_075P_□	0.0027	13.0	8.5	5.0	10.0	0.6	341250272_100P_□
0.0033	10.0	9.0	5.5	7.5	0.6	341000332_075P_□	0.0039	13.0	8.5	5.0	10.0	0.6	341250392_100P_□
0.0047	10.0	10.0	6.0	7.5	0.6	341000472_075P_□	0.0056	13.0	9.5	5.5	10.0	0.6	341250562_100P_□
0.0056	10.0	10.5	6.5	7.5	0.6	341000562_075P_□	0.0068	13.0	10.0	6.0	10.0	0.6	341250682_100P_□
0.0022	13.0	8.5	4.5	10.0	0.6	341000222_100P_□	0.0082	13.0	10.5	6.5	10.0	0.6	341250822_100P_□
0.0027	13.0	8.5	5.0	10.0	0.6	341000272_100P_□	0.0068	18.0	8.5	5.5	15.0	0.8	341250682_150P_□
0.0033	13.0	9.0	5.5	10.0	0.6	341000332_100P_□	0.0082	18.0	9.0	5.5	15.0	0.8	341250822_150P_□
0.0068	13.0	9.5	5.5	10.0	0.6	341000682_100P_□	0.012	18.0	9.5	6.0	15.0	0.8	341250123_150P_□
0.033	15.7	13.4	9.6	12.5	0.8	341000333_125P_□	0.015	18.0	10.0	6.5	15.0	0.8	341250153_150P_□

备注：“—”表示容量偏差。

“□”表示引线方式和长度